



# Catalogue

Band Saw Machine



GB4280 Horizontal Band Sawing

**V-FLO GROUP OF COMPANIES LTD.**

[WWW.V-FLO.COM](http://WWW.V-FLO.COM)

# Performance

**Double-Housing:** To insure the reliability of the Saw when it's working, improve the sawing quality of the workpiece, prolong the lifetime of the Saw Blade. The adjustment of the Working depth is 0-800mm.

**Double-Stepless Speed Regulation:** Adopt Double-Stepless Speed Regulation of the Liner Velocity and the Moving Path for the Saw to running-in the various velocity, so the service lifetime of the Saw can be sured.

**Stepless Speed Regulation for The Cut Line Velocity.**

**Stepless Speed Regulation for The Cut Feeding Velocity, it's optional according to the different materials.**

**Hydraulic Pressure Clamping:** Automatic Tracking for the Hydraulic System, it can control the Feeding, to cut

# Technologic Parameter

Sawing Maching Type:GB4280

Dimension: (mm) : 3000×2000×2000

Weight: 3.5T

The Operating Board fixed the Max Workpiece: Φ800mm

Electrical Feeding Device, the length of the Feeding Facility is optional according to customers' demand.

Main Motor Power: 5.5KW

Oil Motor Power:3K

Total Power:9.5KW

Oil Pump Specification: 10L/min

Saw Strip Dimension: (mm): 6482×54×1.6

# Following Accessories attached the Machine

Operation & Maintain Manual :1PCS

Solenoid valve for Hydraulic System: 2PCS

Governing Volve: 2PCS

Speed Regulation Board for Electric Equipment System: 2PCS

Electric Equipment Switch: 1 Set

Gear Pump: 1 PCS

Pressure Gauge: 2PCS

Steelwire Brush: 5PCS

Bearing: 1 Set

Saw Belt: 1PCS

Band Saw Blade: 6482\*54\*1.6 Japan AMADA